



Type	LONGITUDINAL Movement [mm]	Weight [Kg/Pc]
AGFLEXJ 250	±125	340

\*On Request The Joint Could Be Produced According To Different Standard And Different Compound

POS.	DESCRIPTION	NOTE	STANDARD	MATERIAL
12	Concrete	-	-	-
11	Asphalt	-	-	-
10	Anchor Bar Grouting	-	-	Kimitech EP-AR
9	Drain Pipe	-	(on request)	PVC øi16 øe22 mm
8	Transition Strip	-	(not supplied)	Wabocrete II
7	Bedding Mortar	-	(not supplied)	Masterflow 524
6	Two-Component Epoxide Primer	-	(if necessary)	-
5	Bolt Hole Sealer	-	-	Tecnoseal 88
4	Thixotropic Epoxide Bonding System	-	-	Kimitech EP-TX
3	Waterproof Strip	-	-	NW fabric + rubber
2	Anchor Bars + Washers + Nuts	M 20	EN 20898	Cl. 8.8 Zinc Plated Steel
1	Expansion Joint	-	CNR 10018*	Rubber 60 ShA + Steel

DATE	10/02/2014	OBJECT	Installation materials	REVISION	08
OBJECT	AGFLEXJ 250 JOINT "2T" INSTALLATION PROCEDURE			DRAWN NOT IN SCALE	
AGOM INTERNATIONAL S. r. l. Via Mesero, 12 20010 Ossona (MI)				DRAWN: GR CHECKED: DC APPROVED: MB DWG N°	00413
COPYRIGHT RESERVED TO AGOM INTERNATIONAL SRL					