



Type	LONGITUDINAL Movement [mm]	Weight [Kg/pcs]
AGWJ 100	±50	12

** HIGH CHEMICAL RESISTANCE HYPERFLUID STRUCTURAL MORTAR KERABUILD ANCORAGGI OR SIMILAR (EMACO SFR / EMACOFASST FIBER)
 *On Request The Joint Could Be Produced According To Different Standard And Different Compound

POS.	DESCRIPTION	NOTE	STANDARD	MATERIAL
6	Drain Pipe	(on request)	-	PVC ø16 øe22
5	Asphalt	-	-	-
4	Concrete	-	-	-
3	Fiber Reinforced Mortar	-	-	**
2	Anchor Bars + Washers + Nuts M12	-	EN 20898	Cl. 8.8 Zinc Plated Steel
1	Expansion Joint	-	CNR 10018*	Rubber 60 ShA + Steel

DATE	OBJECT	REVISION
25/01/2010	AGOM MARK	02
AGWJ 100 JOINT "1T" INSTALLATION PROCEDURE		DRAWN NOT IN SCALE DRAWN: DC CHECKED: MB APPROVED: RC
AGOM IDEAS, ENGINEERING AND MANUFACTURE		AGOM INTERNATIONAL S. r. l. Via Mesero, 12 20010 Ossona (MI) DWG N° 00825/1T