



Vertical static load = - kN
 Vertical dynamic load = - kN
 MAX Displacement = ± mm
 Horizontal stiffness = kN/mm
 Damping = -%

Note A: Protective Anticorrosion Cycle According to EN 1337-9

1	Sand-blasting at white metal SA2.5
2	Bicomponent epoxidic covering at high thickness
	Minimum thickness dry film
	a) Exposed surfaces: 250 micron
	b) Worked surfaces and contact surfaces of the concrete: 70 micron

Num.	Q.ty	Description	Material	Notes
11	1	Reinforcement steel plate	S235JR - EN10025	-
10	1	Damping element	Lead	-
9	1	Counter plate	S275JR - EN10025	A
8	1	Lower plate	S275JR - EN10025	A
4	1	Vulcanized plate	S275JR - EN10025	A
3	8	Anchor Bar	S275JR - EN10025	-
2	7	Reinforcement steel plate	S235JR - EN10025	-
1	1	Rubber element	NR 60	A

Revision	00	Object	FIRST ISSUE	Date Last modified	24/02/2014
Drawn by	G.Ruco	Checked by	D.Colombo	Approved by	M.Battaini

	AGOM INTERNATIONAL Srl Via Mesero, 12 20010 Ossona (MI)	Drawing number	Scale
		01503CD	1:4

The information contained in this drawing is the sole property of AGOM INTERNATIONAL Srl. Any reproduction in part or whole without permission is prohibited.

